

TECHNICAL REPORT

LAC 650 SL



M2/B1/BS

APPLICATIONS

- Marquee walling fabric
- Small structures

PRODUCT INFORMATION

| | |
|------------|---|
| WIDTH | 2.50 m and 3.00 m |
| WEIGHT | 680 g/m ² |
| BASE CLOTH | high tenacity polyester 1100 dTex |
| COATING | PVC coating, system LOWICK ® Protection Anti UV |
| FINISH | CLEANGARD ® lacquer both sides |
| COLOUR | Colour range |

PRODUCT CHARACTERISTICS

| | | |
|-------------------------|--------------------|----------------|
| TENSILE STRENGTH | 260/250 daN | NF EN ISO 1421 |
| TEAR STRENGTH | 32/28 daN | DIN 53363 |
| ADHESION | 8 daN / 5 cm | NF EN ISO 2411 |
| TEMPERATURE STABILITY : | | |
| in ° Celsius | - 30°C to + 70°C | |
| in ° Fahrenheit | - 22°F to +158°F | |
| F / R | M2/B1/BS | |
| | NFPA 701 / B-s2-d0 | |

Average values +/- 10 % non contractual



415 avenue de Savoie – SAINT-CLAIR-DE-LA-TOUR – 38357 La Tour du Pin
FRANCE

Tél. 33 (0)4 74 83 51 00 – Fax 33 (0)4 74 83 51 01

www.dickson-coatings.com